

RK19H Tractor



**MORE TRACTOR.
LESS PRICE.**



HYDROSTATIC

**YOUR ONLY
LIMIT
IS YOUR
IMAGINATION**

Tractor & Quick-Attach Loader Price

\$10,599⁹⁸

Monthly Payment as low as

\$158*

*See store location for complete eligibility, details and restrictions. Loans are subject to RFCU membership eligibility and creditworthiness at consummation. RFCU is an equal opportunity lender. Example based upon sales price of tractor and loader model with no down payment, 6.49% APR and equal monthly payment amounts for 84 months. APR is current as of 5/1/19 and your APR may be different. Taxes, delivery and/or insurance charges could increase monthly payments. Insurance is required for tractor loans. Prices are subject to change. RFCU and RK are separate entities. RFCU does not warrant, guarantee, or insure any product or service offered by RK.

Tractor

1.9HP EPA Tier 4 Yanmar Diesel Engine
PTO: 13 PTO HP, RPM Mid/Rear 2500/540
2-Range Hydrostatic Transmission
4WD, Differential Lock
Category 1 3-Pt. Hitch
Hitch Lift Capacity 1,100 lbs (679 lbs 24 in. Behind Link Ends)
Weight: 1433 lbs.
Multiple Tire Options: R4 Industrial (Std), R3 Turf (Opt)

\$8,599⁹⁹

Performance Matched Equipment

RK XB 48" Rotary Tiller
RK XB 48" Rotary Cutter
RK XB 60" Rear Blade
RK XB 60" Yard Rake
RK XB 48" Box Blade
RK XB Middle-Buster/Sub-Soiler
RK 1.5 Ton Dump Trailer w/Hydraulic Pump
Carry On Dual Brake 7' x 20' Transport Trailer
RK by Top Dog G54 Granite Grapple

Loader

L72 Front-End Loader
Skid-Steer Compatible Quick-Attach
Max Lift Height: 72"
Lift Capacity to Full Height: 617 lbs.
Breakout Force: 1,285 lbs.
Bucket Capacity: 4.9 Cu. Ft.
Total Weight: 470 lbs.

\$1,999⁹⁹

Available Accessories

Engine Block Heater
Category 1 Quick Hitch
Sunshade/Canopy
Ballast Box
3rd. Function Valve Kit

Mid Mower

M48 Mid-Mount Mower
Cutting Width: 48"
Height Adjustment Range: 1-4"
Weight: 176 Lbs.

\$1,599⁹⁹

M54 Mid-Mount Mower

Cutting Width: 54"
Height Adjustment Range: 1-4"
Weight: 205 Lbs.

\$1,799⁹⁹

About RK Tractors

RK Tractors are made by TYM, manufacturers of compact tractors for leading U.S. tractor brands. 3-Pt. equipment is made by King Kutter, Winfield AL, and tires & wheels are made by midwest-based Titan International. RK provides full service at every RK Tractor location, zero down payment financing for up to 84 months, tractor delivery (for a fee) and an industry leading 8-year limited powertrain warranty. We can offer fully-loaded, premium tractors at very low prices because we buy directly from the manufacturer. There is no better value anywhere.

All prices subject to change.

RKTRACTORS.COM

SUB-COMPACT TRACTOR SPECIFICATIONS



Model

Engine Make/Model
Gross Engine HP (kW)
PTO HP (kW)
Rated Engine Speed
Number of Cylinders
Displacement cu.in. (cc)
Alternator
Fuel System Type
Fuel Tank Capacity, U.S. gal. (L)

Implement g/m (l/m)
Steering g/m (l/m)
Total Capacity g/m (l/m)
Hitch Lift Capacity, lb. (kg)
At 24" behind link ends, lb. (kg)
Lift Control Type
No. of Standard Remote Valves

Transmission Type
Max Traveling speed (MPH) (km/h)
Brakes
Cruise Control

PTO Type
PTO Control
PTO Mid (rpm)
PTO Rear (rpm)

Overall Length, in. (mm)
Overall Width, in. (mm)
Wheelbase, in. (mm)
Height to top of ROPS, in. (mm)
Min. Ground Clearance, in. (mm)
Total weight, lb (kg)

Standard
Optional
Tire & Wheel Manufacturer

	RK19 Hydrostatic	RK24 Hydrostatic
Engine		
Engine Make/Model	Yanmar 3TNV74F	Yanmar 3TNV80F
Gross Engine HP (kW)	19 (14.2)	24 (17.8)
PTO HP (kW)	13 (9.7)	18.8 (14.0)
Rated Engine Speed	3000	3000
Number of Cylinders	3	3
Displacement cu.in. (cc)	60.6 (993)	77.3 (1267)
Alternator	12V 40A	12V 40A
Fuel System Type	Indirect Fuel Injection	Indirect Fuel Injection
Fuel Tank Capacity, U.S. gal. (L)	6.6 (25)	5.81 (22)
Hydraulics		
Implement g/m (l/m)	4.17 (15.8)	4.18 (15.8)
Steering g/m (l/m)	2.11 (8)	2.77 (10.5)
Total Capacity g/m (l/m)	6.97 (26.4)	6.95 (26.3)
Hitch Lift Capacity, lb. (kg)	1100 (499)	1
At 24" behind link ends, lb. (kg)	679 (308)	1323 (600)
Lift Control Type	Position	1058 (480)
No. of Standard Remote Valves	N/A	1
Transmission		
Transmission Type	Hydrostatic - 2 Range	Hydrostatic - 2 Range
Max Traveling speed (MPH) (km/h)	7.8 (12.5)	11.2 (18.1)
Brakes	Wet Disc	Wet Disc
Cruise Control	No	Yes
Power Take-Off (PTO)		
PTO Type	Independent	Independent
PTO Control	Electric/Hydro	Electric/Hydro
PTO Mid (rpm)	2500	2000
PTO Rear (rpm)	540	1610 (730)
Dimensions		
Overall Length, in. (mm)	94.2 (2394)	100.5 (2553)
Overall Width, in. (mm)	44.5 (1130)	45.8 (1164)
Wheelbase, in. (mm)	53.1 (1350)	57.5 (1460)
Height to top of ROPS, in. (mm)	86.6 (2200)	91.3 (2320)
Min. Ground Clearance, in. (mm)	8.3 (210)	9.4 (240)
Total weight, lb (kg)	1433 (650)	1610 (730)
Tires		
Standard	R3-F 18x8.5-10 R 27x10.5-15	R4-F 20x8-10 R 27x12.5-15
Optional	R4-F 18x8.5-10 R 26x12-12	R3-F 20x8-10 R 29x12.5-15
Tire & Wheel Manufacturer	Titan (USA)	Titan (USA)

Loaders

RK Loader Model RK Tractor Model	L72	L75
	RK19	RK24
Maximum lift height to bucket pivot, in.	71.3	75.3
Lift capacity to maximum height at pivot pin lb.	617	947
Breakout force at ground level, pivot pins, lb.	1,285	1,680
Dumping clearance, in.	53.1	57.4
Dumping reach at maximum lift height, in.	28.3	24.9
Maximum dump angle, degrees.	38	38
Reach with bucket on ground, in.	52.4	51.3
Bucket rollback angle, degrees	20	20
Digging depth, in.	3.9	4.1
Bucket width, in.	48.0	50.0
Total weight loader w/bucket, lb.	470	481
Weight of bucket, lb.	123	132
Bucket capacity, cu/ft.	4.9	5.3
Bucket connection type	Quick-Attach	Quick-Attach

Mid Mowers

RK Mid-Mount Mower Model RK Tractor Model	M48	M54	M60
	RK19	RK19	RK24
Type	Side discharge	Side discharge	Side discharge
Number of blades	3	3	3
Mounting method	Parallel linkage	Parallel linkage	Parallel linkage
Cutting width	48"	54"	60"
Cutting height range	1.0"-4.0"	1.0"-4.0"	1.0"-4.0"
Adjustment of cutting height	Dial gauge	Dial gauge	Dial gauge
Transport height	5.12"	5.12"	5.6"
Wheels	4	4	4
Weight	176 lbs.	205 lbs.	272 lbs.

Backhoe Specifications

RK Backhoe Model RK Tractor Model	BH6.5 RK24 ONLY
Digging Depth (two foot flat bottom)	77"
Mechanical Thumb	Included
Bucket cylinder digging force	2,050 lbs
Dipperstick digging force	1,256 lbs
Reach from center line of Swing Pivot	98"
Loading Height (maximum)	60"
Swing Arc	140"
Transport height (maximum)	66"
Transport Overhang	38"
Bucket Rotation	185"
Stabilizer Spread (down position)	86"
Stabilizer Spread (up position)	50"
Angle of Departure	21"
Shipping weight - backhoe (without bucket)	725 lbs
Standard bucket width	12"
Available bucket sizes	9", 12", 16"