

RK55H Cab Tractor



**MORE TRACTOR.
LESS PRICE.**



HYDROSTATIC

**FULLY LOADED
AND
TURBOCHARGED**

Tractor and Loader Price
\$31,999^{98*}

Monthly Payment as low as
\$475^{*}

*See store location for complete eligibility, details and restrictions. Loans are subject to RFCU membership eligibility and creditworthiness at consummation. RFCU is an equal opportunity lender. Example based upon sales price of tractor and loader model with no down payment, 6.49% APR and equal monthly payment amounts for 84 months. APR is current as of 5/1/19 and your APR may be different. Taxes, delivery and/or insurance charges could increase monthly payments. Insurance is required for tractor loans. Prices are subject to change. RFCU and RK are separate entities. RFCU does not warrant, guarantee, or insure any product or service offered by RK.

Tractor

\$28,599⁹⁹

RK55H Cab Tractor
55HP EPA Tier 4 Turbocharged Yanmar Diesel Engine
PTO: 42.2 PTO HP
3-Range Hydrostatic Transmission
4WD, Differential Lock
Category 1 3-Pt. Hitch, Draft Control
Hitch Lift Capacity 3,314lbs (2,945 lbs 24 in. Behind Link Ends)
2 Sets Rear Hydraulic Remotes Standard
Weight: 4233 lbs.
Titan Tires: R4 Industrial (Std), R1 Ag, R3 Turf (Opt)
Premium Cab: Heat, AC, Audio System, Front & Rear Work Lights

Loader

\$3,399⁹⁹

L110 Front-End-Loader - Includes Rimguard Liquid Tire Ballast
Max Lift Height: 110"
Lift Capacity to Full Height: 2,478 lbs.
Breakout Force: 4,938 lbs.
Bucket Capacity: 11.2 Cu. Ft.
Total Weight: 1,261

Backhoe

\$6,499⁹⁹

BH8.5 Backhoe
Mechanical Thumb Included
Digging Depth 103.2"
Bucket Cylinder Digging Force: 4,435 Lbs.
Dipperstick Digging Force: 2,694 Lbs.
Standard Bucket Width: 18"
Optional Bucket Widths: 9", 12", 16", 24"

Performance Matched Equipment

RK 7 -1/2' Box Frame Disc
RK 72" Kutter W/sc Round Back
RK 72" Finish Mower
RK 84" Pro Box Blade
RK 84" Pro Rear Blade
RK 84" 5500 Rear Blade
RK 72" Pro Tiller
RK 84" Pro Tiller
RK 96" Landscape Rake
Carry On Dual Brake 7' x 20' Transport Trailer
RK by Top Dog G72 Granite Grapple

Available Accessories

Engine Block Heater
Category 1 Quick Hitch
3rd. Function Valve Kit

About RK Tractors

RK Tractors are made by TYM, manufacturers of compact tractors for leading U.S. tractor brands. 3-Pt. equipment is made by King Kutter, Winfield AL, and tires & wheels are made by midwest-based Titan International. RK provides full service at every RK Tractor location, zero down payment financing for up to 84 months, tractor delivery (for a fee) and an industry leading 8-year limited powertrain warranty. We can offer fully-loaded, premium tractors at very low prices because we buy directly from the manufacturer. There is no better value anywhere.

All prices subject to change.

RKTRACTORS.COM

SPECIFICATIONS



Model

Engine Make/Model
 Engine HP (kW) - Gross
 Engine Type
 PTO HP (kW)
 Rated Engine Speed
 Number of Cylinders
 Displacement cu. in. (cc)
 Alternator
 Fuel System Type
 Fuel Tank Capacity, U.S. gal. (L)

Implement g/m (l/m)
 Steering g/m (l/m)
 Total Capacity g/m (l/m)
 Category, 3-Point Hitch
 Hitch Lift Capacity, lb. (kg)
 At 24 inches behind link ends, lb. (kg)
 Lift Control Type
 Joy Stick & Joy Stick Value
 No. of Standard Remote Values
 Draft Control

Transmission Type
 Max. Traveling Speed MPH (km/h)
 Brakes
 Cruise Control

PTO Type
 PTO Control
 PTO Mid (rpm)
 PTO Rear (rpm)

Overall Length, in. (mm)
 Overall Width, in. (mm)
 Wheelbase, in. (mm)
 Height to top of ROPS/Cab, in. (mm)
 Min. Ground Clearance, in. (mm)
 Total Weight, lb. (kg)

Full HVAC - Heating & Air Conditioning
 Audio System
 Front & Rear Work Lights
 Front & Rear Wipers

Standard
 Optional
 Optional
 Tire & Wheel Manufacturer

	55 Shuttle Open Station	55 Hydrostatic Open Station	55 Shuttle Cab	55 Hydrostatic Cab
ENGINE				
Engine Make/Model	Yanmar 4TNV86T-CR	Yanmar 4TNV86T-CR	Yanmar 4TNV86T-CR	Yanmar 4TNV86T-CR
Engine HP (kW) - Gross	55.1 (41.1)	55.1 (44.1)	55.1 (41.1)	55.1 (44.1)
Engine Type	Turbocharged	Turbocharged	Turbocharged	Turbocharged
PTO HP (kW)	44.9 (33.5)	42.2 (31.5)	44.9 (33.5)	42.2 (31.5)
Rated Engine Speed	2800	2800	2800	2800
Number of Cylinders	4	4	4	4
Displacement cu. in. (cc)	127.6 (2091)	127.6 (2091)	127.6 (2091)	127.6 (2091)
Alternator	12V 70A	12V 70A	12V 70A	12V 70A
Fuel System Type	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection
Fuel Tank Capacity, U.S. gal. (L)	17 (60)	17 (60)	17 (60)	17 (60)
HYDRAULICS				
Implement g/m (l/m)	9.5 (36.1)	9.5 (36.1)	9.5 (36.1)	9.5 (36.1)
Steering g/m (l/m)	5.0 (19.0)	5.0 (19.0)	5.0 (19.0)	5.0 (19.0)
Total Capacity g/m (l/m)	14.5 (55.1)	14.5 (55.1)	14.5 (55.1)	14.5 (55.1)
Category, 3-Point Hitch	1	1	1	1
Hitch Lift Capacity, lb. (kg)	3314 (1503)	3314 (1503)	3314 (1503)	3314 (1503)
At 24 inches behind link ends, lb. (kg)	2945 (1336)	2945 (1336)	2945 (1336)	2945 (1336)
Lift Control Type	Position	Position	Position	Position
Joy Stick & Joy Stick Value	Standard	Standard	Standard	Standard
No. of Standard Remote Values	2 Sets	2 Sets	2 Sets	2 Sets
Draft Control	Standard	Standard	Standard	Standard
TRANSMISSION				
Transmission Type	16F/16R Syncro Shuttle w/creeper	Hydrostatic - 3 Range	16F/16R Syncro Shuttle w/creeper	Hydrostatic - 3 Range
Max. Traveling Speed MPH (km/h)	18.4 (29.7)	17.7 (28.4)	15.0 (24.2)	16.8 (27)
Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Disc
Cruise Control	No	Yes	No	Yes
POWER TAKE-OFF (PTO)				
PTO Type	Independent	Independent	Independent	Independent
PTO Control	Electric/Hydro	Electric/Hydro	Electric/Hydro	Electric/Hydro
PTO Mid (rpm)	n/a	n/a	n/a	Option
PTO Rear (rpm)	540	540	540	540
DIMENSIONS				
Overall Length, in. (mm)	141.3 (3590)	141.3 (3590)	141.3 (3590)	141.3 (3590)
Overall Width, in. (mm)	63.8 (1620)	63.8 (1620)	63.8 (1620)	63.8 (1620)
Wheelbase, in. (mm)	76.2 (1935)	76.2 (1935)	76.2 (1935)	76.2 (1935)
Height to top of ROPS/Cab, in. (mm)	102.1 (2594)	102.1 (2594)	99.6 (2530)	99.6 (2530)
Min. Ground Clearance, in. (mm)	13.8 (350)	13.8 (350)	13.8 (350)	13.8 (350)
Total Weight, lb. (kg)	3814 (1730)	3814 (1730)	4233 (1920)	4233 (1920)
CAB FEATURES				
Full HVAC - Heating & Air Conditioning	n/a	n/a	Standard	Standard
Audio System	n/a	n/a	Standard	Standard
Front & Rear Work Lights	n/a	n/a	Standard	Standard
Front & Rear Wipers	n/a	n/a	Standard	Standard
TIRES				
Standard	R4 - F 12x16.5 R 16.9x24	R4 - F 12x16.5 R 16.9x24	R4 - F 12x16.5 R 16.9x24	R4 - F 12x16.5 R 16.9x24
Optional	R1 - F 9.5x16 R 14.9x24	R1 - F 9.5x16 R 14.9x24	R1 - F 9.5x16 R 14.9x24	R1 - F 9.5x16 R 14.9x24
Optional	R3 - F 12x16.5 R 16.9x24	R3 - F 12x16.5 R 16.9x24	R3 - F 12x16.5 R 16.9x24	R3 - F 12x16.5 R 16.9x24
Tire & Wheel Manufacturer	Titan (USA)	Titan (USA)	Titan (USA)	Titan (USA)