

RK74 Cab Tractor



**MORE TRACTOR.
LESS PRICE.**



POWER SHUTTLE

**POWERFUL
UTILITY
TRACTOR**

Tractor and Loader Price

\$42,998

Monthly Payment as low as

\$649*

* See RK Tractor store location for complete eligibility, details, and restrictions. This is not a commitment to make a loan. Loans are subject to borrower qualifications, and subject to approved installment credit with D.L.L., based on D.L.L. financing eligibility guidelines. Example based upon sales price of tractor and loader model with no down payment, 6.99% APR and equal monthly payment amounts for 84 months. Taxes and delivery charges could increase monthly payments. All prices are estimates, variable based upon product options selected, and are subject to change.

Tractor

\$37,999

RK74PSC Cab Tractor
74HP EPA Tier 4 Turbocharged Tier 4 Deutz Diesel Engine
Rear PTO: 64.1 PTO HP 540/750 RPM
16F/16R Power Shuttle w/creeper interlock
4WD, Differential Lock
Category 2 3-Pt. Hitch, Draft Control
Hitch Lift Capacity 5,115 lbs. (3414 lbs. 24 in. Behind Link Ends)
2 Sets Rear Hydraulic Remotes Standard
Weight: 6052 lbs.
Titan Tire & Wheels: R1 Ag, R3 Turf, R4 Industrial
Premium Cab: Heat, AC, Audio System, Front & Rear Work Lights
High-back suspension seat with extension

Loader

\$4,999

L135SL Front-End-Loader - Includes Rim guard
Liquid Tire Ballast
Self-Leveling
Max Lift Height: 135.5"
Lift Capacity to Full Height: 3,223 lbs.
Breakout Force: 5,335 lbs.
Bucket Capacity: 13.8 Cu. Ft.
Total Weight: 1,889 lbs.
Skid-steer compatible quick coupler

About RK Tractors

RK Tractors are made by TYM, manufacturers of compact & utility tractors for leading U.S. tractor brands. 3-Pt. equipment is made by King Kutter, Winfield AL, and tires & wheels are made by Midwest-based Titan International. RK provides full service at every RK Tractor location, zero down payment financing for up to 84 months, tractor delivery (for a fee) and an industry leading 8-year limited powertrain warranty for 19-55HP tractors, and 5-year limited powertrain warranty for 74HP tractors. We can offer fully-loaded, premium tractors at very low prices because we buy directly from the manufacturer. There is no better value anywhere.

All prices subject to change.

RKTRACTORS.COM

SPECIFICATIONS



Model

	RK74 Shuttle Shift Cab	RK74 Power Shuttle Cab
ENGINE		
Engine Make/Model	Deutz TCD2.9 L4	Deutz TCD2.9 L4
Engine HP (kW) - Gross	74 (55.4)	74 (55.4)
Engine Type	Turbocharged	Turbocharged
PTO HP (kW)	64.1 (47.8)	64.1 (47.8)
Rated Engine Speed	2200	2200
Number of Cylinders	4	4
Displacement cu. in. (cc)	177.0 (2900)	177.0 (2900)
Alternator	12V 95A	12V 95A
Fuel System Type	Common Rail Direct Injection	Common Rail Direct Injection
Fuel Tank Capacity, U.S. gal. (L)	23.8 (90)	23.8 (90)
HYDRAULICS		
Implement g/m (l/m)	10.3 (39.1)	10.3 (39.1)
Steering g/m (l/m)	5.8 (22)	5.8 (22)
Total Capacity g/m (l/m)	16.1 (61.1)	16.1 (61.1)
Category, 3-Point Hitch	2	2
Hitch Lift Capacity, lb. (kg)	5115 (2320)	5115 (2320)
At 24 inches behind link ends, lb. (kg)	3414 (1550)	3414 (1550)
Lift Control Type	Position/Draft/Mech	Position/Draft/Mech
Joy Stick & Joy Stick Value	Standard	Standard
No. of Standard Remote Values	2 Sets	2 Sets
Draft Control	Standard	Standard
TRANSMISSION		
Transmission Type	16F/16R Syncro Shuttle w/creeper	16F/16R Power Shuttle w/creeper
Max. Traveling Speed MPH (km/h)	18.9 (30.4)	18.9 (30.4)
Brakes	Wet Disc	Wet Disc
Cruise Control	No	Yes
POWER TAKE-OFF (PTO)		
PTO Type	Independent	Independent
PTO Control	Electric/Hydro	Electric/Hydro
PTO Rear (rpm)	540/750	540/750
PTO Shaft Diameter mm	35	35
DIMENSIONS		
Overall Length, in. (mm)	157.5 (4002)	157.5 (4002)
Overall Width, in. (mm)	76.4 (1940)	76.4 (1940)
Wheelbase, in. (mm)	86.1 (2188)	86.1 (2188)
Height to top of ROPS/Cab, in. (mm)	103.3 (2624)	103.3 (2624)
Min. Ground Clearance, in. (mm)	18.3 (465)	18.3 (465)
Total Weight, lb. (kg)	6052 (2745)	6052 (2745)
CAB FEATURES		
Full HVAC - Heating & Air Conditioning	Standard	Standard
Audio System	Standard	Standard
Front & Rear Work Lights	Standard	Standard
Front & Rear Wipers	Standard	Standard
TIRES		
R1 Agricultural	R4 - F 15x9.5 R 18.4x24	R4 - F 15x9.5 R 18.4x24
R3 Turf	R3 - F 12.0x20.5 R 22.4x25.5	R3 - F 12.0x20.5 R 22.4x25.5
R4 Industrial	R1 - F 11.2x24 R 16.9x30	R1 - F 11.2x24 R 16.9x30
Tire & Wheel Manufacturer	Titan (USA)	Titan (USA)

LOADERS	
RK Loader Model	L135SL
RK Tractor Model	RK74
Maximum lift height to bucket pivot, in.	135.5
Lift capacity to maximum height at pivot pin lb.	3,223
Breakout force at ground level, pivot pins, lb.	5,335
Relief Valve Setting (Loader Control Valve), PSI	2,489
Rated Flow (Tractor System), gpm	11
Lift Cylinder, in.	2.8 x 1.6
Bucket Cylinder, in.	2.8 x 1.6
Boom Raising Time, sec.	7
Boom Lowering Time, sec.	4.7
Bucket Rollback Time, sec.	3.2
Bucket Dumping Time, sec.	4.8
Dumping Clearance, in.	104.3
Dumping Reach at Maximum lift height, in.	21.4
Maximum Dump Angle, degrees	53
Reach at Maximum Lift Height, in.	23
Reach with Bucket on Ground, in.	85.4
Bucket Rollback Angle, degrees	35
Digging Depth, in.	7.7
Bucket Width, in.	84.0
Total Weight Loader w/Bucket, lbs.	1,889
Weight of Bucket, lbs.	399
Bucket Capacity, cu/ft.	13.8
Bucket Connection Type	Quick Coupler
Bucket Level Indicator	Std

