

# RK24H Tractor



**MORE TRACTOR.  
LESS PRICE.**



**HYDROSTATIC**

**THE RIGHT  
AMOUNT OF  
POWER WHEN  
YOU NEED IT.**

Tractor & Quick-Attach Loader Price

**\$12,798**

Monthly Payment as low as

**\$193\***

\*See RK Tractor store location for complete eligibility, details and restrictions. This is not a commitment to make a loan. Loans are subject to borrower qualifications, and subject to approved installment credit with D.L.L., based on D.L.L. financing eligibility guidelines. Example based upon sales price of tractor and loader model with no down payment, 5.99% APR and equal monthly payment amounts for 84 months. Taxes and delivery charges could increase monthly payments. All prices are estimates, variable based upon product options selected, and are subject to change.

## Tractor

24HP EPA Tier 4 Yanmar Diesel Engine  
PTO: 18.8 PTO HP, RPM Mid/Rear 2500/540  
2-Range Hydrostatic Transmission  
4WD, Differential Lock  
Category 1 3-Pt. Hitch  
Hitch Lift Capacity 1,323 lbs (1,058 lbs 24 in. Behind Link Ends)  
1 Set Rear Hydraulic Remotes Standard  
Weight: 1610 lbs.  
Titan Tires: R4 Industrial (Std), R3 Turf (Opt)

**\$10,499**

## Mid Mower

M60 Mid-Mount Mower  
Cutting Width: 60"  
Height Adjustment Range: 1-4"  
Weight: 272 Lbs.

**\$1,999**

## Performance Matched Equipment

RK XBX 54" Rotary Tiller  
RK XB 48" Rotary Cutter  
RK XB 60" Rear Blade  
RK XB 60" Yard Rake  
RK XB 48" Box Blade  
RK XB Middle-Buster/Sub-Soiler  
RK 1.5 Ton Dump Trailer w/Hydraulic Pump  
Carry On Dual Brake 7' x 16' Transport Trailer

## Available Accessories

Engine Block Heater  
Category 1 Quick Hitch  
Sunshade/Canopy  
Ballast Box

## About RK Tractors

RK Tractors are made by TYM, manufacturers of compact tractors for leading U.S. tractor brands. 3-Pt. equipment is made by King Kutter, Winfield AL, and tires & wheels are made by midwest-based Titan International. RK provides full service at every RK Tractor location, zero down payment financing for up to 84 months, tractor delivery (for a fee) and an industry leading 8-year limited powertrain warranty. We can offer fully-loaded, premium tractors at very low prices because we buy directly from the manufacturer. There is no better value anywhere.

## Loader

L75 Front-End Loader  
Skid-Steer Compatible Quick-Attach  
Max Lift Height: 75"  
Lift Capacity to Full Height: 947 lbs.  
Breakout Force: 1,680 lbs.  
Bucket Capacity: 5.3 Cu. Ft.  
Total Weight: 481 lbs.

**\$2,299**

## Backhoe

BH6.5 Backhoe  
Mechanical Thumb Included  
Digging Depth 77"  
Bucket Cylinder Digging Force: 2,050 lbs.  
Dipperstick Digging Force: 1,256 lbs.  
Standard Bucket Width: 12"  
Optional Bucket Widths: 9", 16", 18"

**\$4,999**

All prices subject to change.

**RKTRACTORS.COM**

# SUB-COMPACT TRACTOR SPECIFICATIONS



## Model

	RK19 Hydrostatic	RK24 Hydrostatic
<b>Engine</b>		
Engine Make/Model	Yanmar 3TNV74F	Yanmar 3TNV80F
Gross Engine HP (kW)	19 (14.2)	24 (17.8)
PTO HP (kW)	13 (9.7)	18.8 (14.0)
Rated Engine Speed	3000	3000
Number of Cylinders	3	3
Displacement cu.in. (cc)	60.6 (993)	77.3 (1267)
Alternator	12V 40A	12V 40A
Fuel System Type	Indirect Fuel Injection	Indirect Fuel Injection
Fuel Tank Capacity, U.S. gal. (L)	6.6 (25)	5.81 (22)
<b>Hydraulics</b>		
Implement g/m (l/m)	4.17 (15.8)	4.18 (15.8)
Steering g/m (l/m)	2.11 (8)	2.77 (10.5)
Total Capacity g/m (l/m)	6.97 (26.4)	6.95 (26.3)
Hitch Lift Capacity, lb. (kg)	1100 (499)	1
At 24" behind link ends, lb. (kg)	679 (308)	1323 (600)
Lift Control Type	Position	1058 (480)
No. of Standard Remote Valves	N/A	1
<b>Transmission</b>		
Transmission Type	Hydrostatic - 2 Range	Hydrostatic - 2 Range
Max Traveling speed (MPH) (km/h)	7.8 (12.5)	11.2 (18.1)
Brakes	Wet Disc	Wet Disc
Cruise Control	No	Yes
<b>Power Take-Off (PTO)</b>		
PTO Type	Independent	Independent
PTO Control	Electric/Hydro	Electric/Hydro
PTO Mid (rpm)	2500	2000
PTO Rear (rpm)	540	1610 (730)
<b>Dimensions</b>		
Overall Length, in. (mm)	94.2 (2394)	100.5 (2553)
Overall Width, in. (mm)	44.5 (1130)	45.8 (1164)
Wheelbase, in. (mm)	53.1 (1350)	57.5 (1460)
Height to top of ROPS, in. (mm)	86.6 (2200)	91.3 (2320)
Min. Ground Clearance, in. (mm)	8.3 (210)	9.4 (240)
Total weight, lb (kg)	1433 (650)	1610 (730)
<b>Tires</b>		
Standard	R3-F 18x8.5-10 R 27x10.5-15	R4-F 20x8-10 R 27x12.5-15
Optional	R4-F 18x8.5-10 R 26x12-12	R3-F 20x8-10 R 29x12.5-15
Tire & Wheel Manufacturer	Titan (USA)	Titan (USA)

Engine Make/Model  
Gross Engine HP (kW)  
PTO HP (kW)  
Rated Engine Speed  
Number of Cylinders  
Displacement cu.in. (cc)  
Alternator  
Fuel System Type  
Fuel Tank Capacity, U.S. gal. (L)

Transmission Type  
Max Traveling speed (MPH) (km/h)  
Brakes  
Cruise Control  
PTO Type  
PTO Control  
PTO Mid (rpm)  
PTO Rear (rpm)

Overall Length, in. (mm)  
Overall Width, in. (mm)  
Wheelbase, in. (mm)  
Height to top of ROPS, in. (mm)  
Min. Ground Clearance, in. (mm)  
Total weight, lb (kg)

Standard  
Optional  
Tire & Wheel Manufacturer

## Loaders

RK Loader Model RK Tractor Model	L72	L75
	RK19	RK24
Maximum lift height to bucket pivot, in.	71.3	75.3
Lift capacity to maximum height at pivot pin lb.	617	947
Breakout force at ground level, pivot pins, lb.	1,285	1,680
Dumping clearance, in.	53.1	57.4
Dumping reach at maximum lift height, in.	28.3	24.9
Maximum dump angle, degrees.	38	38
Reach with bucket on ground, in.	52.4	51.3
Bucket rollback angle, degrees	20	20
Digging depth, in.	3.9	4.1
Bucket width, in.	48.0	50.0
Total weight loader w/bucket, lb.	470	481
Weight of bucket, lb.	123	132
Bucket capacity, cu/ft.	4.9	5.3
Bucket connection type	Pin-on	Pin-on

## Mid Mowers

RK Mid-Mount Mower Model RK Tractor Model	M48	M54	M60
	RK19	RK19	RK24
Type	Side discharge	Side discharge	Side discharge
Number of blades	3	3	3
Mounting method	Parallel linkage	Parallel linkage	Parallel linkage
Cutting width	48"	54"	60"
Cutting height range	1.0"-4.0"	1.0"-4.0"	1.0"-4.0"
Adjustment of cutting height	Dial gauge	Dial gauge	Linkage
Transport height	5.12"	5.12"	5.6"
Wheels	4	4	4
Weight	176 lbs.	205 lbs.	272 lbs.

## Backhoe Specifications

RK Backhoe Model RK Tractor Model	BH6.5 RK24 ONLY
Digging Depth (two foot flat bottom)	77"
<b>Mechanical Thumb</b>	Included
Bucket cylinder digging force	2,050 lbs
Dipperstick digging force	1,256 lbs
Reach from center line of Swing Pivot	98"
Loading Height (maximum)	60"
Swing Arc	140°
Transport height (maximum)	66"
Transport Overhang	38"
Bucket Rotation	185°
Stabilizer Spread (down position)	86°
Stabilizer Spread (up position)	50°
Angle of Departure	21°
Shipping weight - backhoe (without bucket)	725 lbs
Standard bucket width	12°
Available bucket sizes	9', 12', 16°